







imagePROGRAF TX-3000 MFP T36

## imagePROGRAF

## TX-3000 MFP T36

## PRINTER SPECIFICATIONS (see usa.canon.com for full printer specs)

#### **Print Head**

PF-06

#### **Number of Nozzles**

Matte Black: 5,120 Nozzles Other Colors: 2,560 Nozzles per Color

#### **Droplet Size**

5 Picoliter

Ink Type
Pigment: Matte Black (MBK), Cyan (C), Magenta (M), Yellow (Y), Black (BK)

Shipped with Printer: PFI-310 (330 ml) MBK; PFI-110 (160 ml) BK, C, M, Y

Replacement: PFI-110 (160 ml), PFI-310 (330 ml), or PFI-710 (700 ml)

### **Printer RAM**

128 GB (Virtual), 2 GB (Physical)

## **Hard Drive**

#### **Media Feed**

Roll Feed: One Roll, Front-loading, Front Output

## Media Width

Roll Feed: 8"-36"(203.2 mm -914.4 mm) Cut Sheet: 8"-36"(203.2 mm -914.4 mm)

#### **Media Cutter**

Durable Dual-Blade Rotary Cutter

#### **Media Thickness**

 $0.07 - 0.8 \, \text{mm}$ 

## **Media Core Sizes**

2" and 3" Core Adapters Included

#### **Maximum Roll Outer Diameter** 6.7" (170 mm)

Media Output

TX Stacker (Standard)

#### **Printing Software Utilities**

Accounting Manager, Apple AirPrint, <sup>†</sup> Canon Print Service, Device Management Console, Direct Print & Share, Free Layout Tool, imagePROGRAF Printer Driver for Windows\*/ Mac\*, Media Configuration Tool, PosterArtist Lite for Windows, Printer Driver Extra Kit for Windows/Mac (Free Print Utility Layout, Advanced Preview), Optimized Driver for AutoCAD, Print Plug-in for Microsoft\* Word/Excel/PowerPoint\* for Windows, Quick Utility Toolbox

**Operating System** Windows 7 (32/64 bit), Windows 8.1 (32/64 bit), Windows 10 (32/64 bit), Windows Server 2008 R2, (32/64 bit), Windows Server 2012 (64 bit), Windows Server 2012 R2 (64 bit), Windows Server 2016 (64 bit), Macintosh OS X v10.10.5-v10.12x

**Print Language Printer:** SGRaster, HP-GL/2, HP RTL, PDF, JPEG

Standard (Built-in): USB 2.0 Hi-Speed, 10/100/1000Base-T/TX, Wireless LAN (IEEE 802.11 b/g/n) Direct USB Thumb Drive Printing

Power Supply AC 100-240V (50-60 Hz)

### **Power Consumption**

Maximum: 105 W or Less Standby: 3.6 W or Less

Power Off: 0.3 W or Less (Executive Order Compliant)

### Certifications

Electrical Safety Regulations
C TUVus (U.S.A.), C TUVus (Canada)
Electromagnetic Interface Regulations
FCC Part 15B (U.S.A.), IC (Canada)

Radio Regulations FCC Part 15C (U.S.A.), IC (Canada)

Environmental Certifications ENERGY STAR\* (Worldwide)

Operational Environment Temperature: 59° - 86° F (15° - 30° C) Relative Humidity: 10 - 80% (Non Condensation)

## Printer Dimensions (H x W x D) and Weight

(With Stacker Opened) 46.0" x 54.7" x 46.8" Approx. 257 lb

## Package Dimensions (H x W x D) and Weight

#### With Stand and Pallet

41.8" x 63.2" x 35.6" Approx. 337 lb.

# **Stacker** 11.5" x 49.2" x 35.7" Approx. 53 lb.

Roll Unit 18.1" x 60.0" x 22.1" Approx. 57 lb.

#### **Options**

- Multifunction Roll System (RU-32)
- 2"/3" Roll Holder Set (RH2-34)
- PosterArtist

- User-Replaceable Items
   Ink Tank (PFI-110/PFI-310/PFI-710)
- Print Head (PF-06)
  Maintenance Cartridge (MC-30)
  Cutter Blade (CT-07)

#### What's In The Box

Printer, TX Stacker, Stand, 2"/3" Core Media Spool (Adapters Included), Power Cord, Tools and Screws, Print Head, Maintenance Cartridge (Installed), 5 Ink Tanks (330 ml: MBK, 160 ml: BK/C/M/Y), Sample Heavyweight Coated Paper (A2/5 Sheets), Ethernet Card (built-in), USB 2.0 High-speed Interface, USB Connection Sheet, WDS Conics Target Legislation (2018). iWR Service Terms Leaflet, User Manual, Quick Setup Guide, User Software CD for Windows (Printer Driver Utilities), PosterArtist Lite CD, User Registration Card

## T36 SCANNER SPECIFICATIONS

- Scan Speed\*\*
   48-bit Full Color @ 200 dpi: 6" (per second)
- 16-bit Grayscale and Monochrome @ 200 dpi: 13" (per sécond)

### Scan Modes

- 16.7-million Color RGB (24-bit)256-level Grayscale (8-bit)
- Black and White (1-bit)

## **Color Space**

sRGB

## **Maximum Resolution**

1200 dpi (optical)

## Scan Accuracy

+/- 0.1%; +/- 1 pixel Maximum Scan Width

**Maximum Media Width** 

Maximum Scan Length 315" (JPEG/PDF), 598" (TIFF)

#### **Maximum Media Thickness** 0.079" (2 mm)

## Media Feed System

Adaptive CIS media focus management and media guide mechanism; intuitive face-up, front-loading, and front/rear-exit media path; automatic media size detection with optical media sensors

## **Digital Imaging Technology**

Contact Image Sensor (CIS) Technology (SingleSensor Assembly)

- 48-bit RGB digital color image capture
  16-bit grayscale image capture

- Panchromatic monochrome and black and white
   Bi-directional extra long-life LED light system for optimum object illumination and instant-on scanning capability

- Digital Image Processing

   2D Intelligent Adaptive Thresholding (IAT) (1-bit mode)

   Fixed Threshold Black and White (1-bit mode)

## **User Status and One-Touch Operation**

Right-side mounted control panel; walk-up operation and user selection of stop, forward and rewind, scan, copy, or copy and archive

## **Included Software**

SmartWorks MFP Scan-to-Copy/File/Email with Real-time Image Viewer; supports TIFF, JPEG, TIFF G4, and PDF

**Operating System**Windows 10 Enterprise LTSB (x64)

## Scanner Interface Kit

Superspeed USB 3.0 (PC Connector Compatible with USB 2.0 and USB 3.0 sockets)

## **Operating Environments**

10 - 35°C, 35-80% RH, Non-condensing

External Power Supply 100-240 VAC Autosensing +/- 10%, 50-60Hz

## **Scanner Power Consumption**

- 53 Wh (scanning) 5 Wh (stand-by)

Compliances
VCCI, CB, CE, FCC, UL, RoHS, ENERGY STAR®

### **Scanner Dimensions** Height:

43.6" 14.4" Width: Depth: **Scanner Weight** 

## Approx. 33.1 lb. MFP Package Dimensions (H x W x D) and Weight

With Stand, Pallet, and Scanner

57.3" x 63.3" x 36.0" Approx. 448 lb

## What's In The Box?

- T36 Scanner with Power Cord, USB 3.0 Cable
- · Power Supply
- Ethernet Cable
- Stand

- Stand
   (2) Paper Edge Guides
   (3) Document Return Guides
   All-in-One Touch Screen Computer
   USB Drive with SmartWorks MFP Software,
  Scanner User Manual, and Quick Start Guide
- Calibration Target
- T36 Scanner Quick Start Guide
- † To be supported in 2018 by updating firmware.
- Wireless printing requires a working network with wireless 802.11b/g or 802.11n capability. Wireless performance may vary based on terrain and distance between the printer and wireless network clients.
- The scan rate is proportional across the full range of resolutions supported by the scanner. Actual scan times will depend on the host system performance. Quoted top speeds may be limited by the effective bandwidth of the USB 2 and is not guaranteed for all media types
- ▲ The quoted scan accuracy may vary depending on the operating environment and the thickness of the media

Note: The imagePROGRAF TX Series MFP T36 systems contain multiple components, some of which are manufactured by third parties. To the extent that such third-party offerings come with limited warranties, such limited warranties are hereby passed to the purchaser, and Canon shall have no obligation or any liability with respect to such third-party offerings.



















