imagePROGRAF TX-4000 MFP T36

A GAME-CHANGING LARGE-FORMAT MULTIFUNCTION PRINTER; EFFICIENT PRODUCTION AND CLASS-LEADING QUALITY.



- New 5-colour print head and continuous printing capability enable outstanding productivity
- Printing and scanning simultaneously drives further workflow efficiency
- Simple and convenient maintenance thanks to dual-roll feeding and easy roll replacement
- LUCIA TD ink delivers sharp text and fine lines, even on economical uncoated paper
- Superb scanning quality, using Colortrac SingleSensor technology to deliver consistent performance
- Intuitive control across print and scan tasks, via 15.6-inch colour touchscreen display and new SmartWorks software
- Scan board media up to 2-mm thick
- Compact design, with scanner closely integrated, helps the TX-4000 fit into small office spaces
- Peace of mind from excellent reliability and impressive security credentials
- Optimised for weather-resistant media printing, perfect for CAD, GIS and outdoor Posters

An advanced 44-inch largeformat multifunction inkjet for high-end CAD, GIS and Poster production. Supreme productivity, outstanding quality, and intuitive operation across printing and scanning tasks.



PRODUCT RANGE



imagePROGRAF TX-3000 MFP T36



imagePROGRAF TX-4000 MFP T36



imagePROGRAF TX-2000





TECHNICAL SPECIFICATIONS

SCANNER TECHNOLOGY Scan Technology Optical Resolution (dpi) Paper path Scan width Min scan width Document width Max scan length Weight of scanner Dimensions W x D x L Power Supply Compliances Front/rear exit Document handling -Face up/down Document thickness (1) Scan speed 8-bit grayscale & mono @200dpi (2) Scan speed 24-bit colour @200dpi (2) Interface USB Scanner controls

Branding/Colour Software (included) OS for software What's in the box

EITHER LCD OPTION CAN BE SELECTED* *Not available in all countries LCD Flat Panel - PC Included (3)

LCD Flat Panel - PC Excluded (3)

PRINTER TECHNOLOGY Printer Type Print Technology

Number of Nozzles

Print Resolution Nozzle Pitch

Ink Capacity Ink Type

OS Compatability

Printer Languages Standard Interfaces

MEMORY Standard memory Expansion slot HARD DISK

FINE



Canon

SingleSensor 1200 Flat 36" (914mm) 6" (15cm) 38" (965mm) 8m (JPEG/PDF), 15.2m (TIFF) 15Kg 1110 x 324 x 153 mm External power supply 100-240VAC autosensing +/-10%, 50-60Hz Energy Star, National: CB, Russia: EAC, EU: CE Rear (front eject via Document Return Guide) Up 2.0mm 13 inches/sec 6.0 inches/sec 3.0 (backward compatible to USB2) Stop, Advance/Rewind, LED status

None / Canon black SmartWorks MFP V6 Win 8.1/10 (64 bit) T36 scanner
Stand assembly - Stand assembly
- 2 paper deg guides
- 2 paper deg guides
- Document return guides (3 for T36)
- Calibration target
- CD for SmartWorks MFP software and PDF documentation:
T25/T36 Scanner User Manual and Quick Start Guide.
- T36 Scanner Guide.
USB3 cable (3 meter)
- Power Supply
Regional - Mains power cord(s) (2 meter)

LCD Type: All in One: 15.6" TFT Display, Multi-touch PC (included): System: Windows 10 Enterprise LTSB, CPU: Intel Celeron G3900 2.3GHz, RAW: 4GB DDR4, HDD: SATA 500GB, 3 × USB3 & 1 USB2 & 1 x GbE (rear), 1 x USB3 (Front) LCD Type: 15.6" Flat Panel Touch-Screen Display

5 Colour - 44"/1117.6mm Canon Bubblejet on Demand 6 colours integrated type (6 chips per print head x 1 print head) Total: 15,360 MBK: 5,120 nozzles C, M, Y, BK: 2,560 nozzles each 2,400 x 1,200 dpi 1,200 x 2 includes Non-firing nozzle detection and compensation system

Bundled Starter Ink: 330ml (MBK,BK,C,M,Y) Pigment ink: 5 colour MBK/BK/C/M/Y Microsoft Windows: 32bit: 7.8.1.10. 64bit: 7.8.1.10. Windows Server: 2008R2, 2012/2012R2, 2016. Apple Macintosh: OS X 10.10.5 - 10.11, MacOS 10.12

HP-GL/2, HP RTL, PDF, JPEG - for details check specifications USB B Port: Type: Built in (Hi-Speed USB)

Mode: Full Speed (12 Mbit/sec), High Speed (480 Mbit/sec), Bulk transfer Connector Port: Series B (4 pins) USB A Port: USB Memory (Direct Print)

USB A PORT: USB Memory (Direct Print) Standard: IEEE 802.3 10base-T IEEE 802.3 u0bobse-TX/Auto-Negotiation IEEE 802.3ab 1000base-T/Auto-Negotiation IEEE 802.3a Full Duplex Protocol: SNMP (Canon-MIB), HTTP, TCP/IP (IPv4/IPv6), ftp Wireless LAN:

Standard: IEEE802.11n/IEEE802.11g/IEEE802.11b Security: WEP (64/128bit) WPA-PSK (TKIP/AES) WPA2-PSK (TKIP/AES)

128GB (Physical memory 2GB) No

500GB (Encrypted)

Media Thickness Minimum Printable Length 203.2mm Maximum Printable Length

Maximum Media Roll Diameter Paper Feed Method

PRINTING SPEED

Plain Paper (AO Roll)

Plain Paper (AO Roll)

PAPER HANDLING

Media Width

Heavy coated Paper (A0 Roll)

CAD Drawing:

Poster:

Borderless Printing Width (Roll Only)

MAXIMUM NUMBERS OF DELIVERED PRINTS Multi-position Basket

Stacker

DIMENSIONS AND WEIGHT Physical Dimensions and Weight

Software Included

WHAT'S INCLUDED What's in the Box?

OPTIONS

Optional Items

CONSUMABLES User Replaceable Items

- Thick documents up to 2mm must be flexible and the paper return guide removed. Some media should be scanned at reduced speeds to obtain optimal image quality. Colortrac cannot guarantee to scan all media. For large media Colortrac recommend the scanner be placed on a flat surface and the operator supports the document as it enters and exits the scanner.
- The scan rate is proportional across the full range of resolutions supported by the scanner. Actual scan times and quoted top speeds will depend on the host performance and are not guaranteed for all times and quoted top speeds will depend on the host performance and are not guaranteed for all media types. True 200 x 200dpi image capture. Competitors quote scan speeds using "Turbo', "Normal" or 'High Speed' modes that reduce image quality whilst suggesting that scan resolution is doubled. These modes use software interpolation to create 'virtual image pixels' from a lower resolution scan thereby increasing the number of pixels in the scan direction (&/or X-direction) in an attempt to simulate higher image resolution. Colortrac SmartLF scanners are designed to scan images fast at the optimum resolution required to capture the original image detail without compromising quality.

3. Please check your local supplier, some LCD options may not be available in your country

Disclaimer

Some images are simulated for clarity of reproduction. All data is based on Canon's standard testing methods. This leaflet and the specifications of the product have been developed prior to the date of product launch. Final specifications are subject to change without notice" and * All company and/or product names are trademarks and/or registered trademarks of their respective manufacturers in their the specific section and the specification are subject to change the specific section. markets and/or countries.

Canon recommends you use Canon Media for the best results. Please check media (paper) compatibility list to see which variety of paper/media is recommended.

Canon Inc. canon.com

Canon Europe canon-europe.com

English edition © Canon Europa N.V.,2018

imagePROGRAF TX-4000 MFP T36

0:37 (Fast Economy Mode) 0:40 (Fast) 1:10 (Standard)

0:42 (Fast Economy mode) 0:42 (Fast) 1:26 (Standard) 1:43 (Fast) 2:37 (Standard)

Roll paper: 203.2 - 1118mm Cut Sheet: 203.2 - 1118mm 0.07 - 0.8mm Roll Paper: 18m (varies according to the OS and application) Cut Sheet: 1.6m

170 mm Roll Paper: Front loading, front output Cut Sheet: Front loading, front output (Manual feed using media locking lever)

(Recommended) 515mm(JIS B2), 594mm(ISO A1), 728mm (JIS B1), 841mm (ISO A0), 10°, 14°, 17°, 24°, 36°, 42°, 44° [Printable] 257mm(JIS B4), 297mm(ISO A3), 329mm(ISO A3+), 420mm (ISO A2), 8°, 12°, 16°, 20°, 30°, 300mm, 500mm, 600mm, 800mm, 1000mm

Standard Position : 1 sheet (any image)

Flat Position : 20 sheets (A2 landscape, any image, plain paper/ Basket Position : 1 sheet (any image)

Folding Position : 100 sheets (A0/A1 portrait, CAD drawing, plain paper)

Stacking Position : 100 sheets (A1/A2 landscape, CAD drawing, plain paper)

imagePROGRAF TX-4000 MFP T36 H1356 x W:1835 x D:766mm Weight:149Kg Printer Depth dimension when the basket is closed. Dimensions and Weight include printer and basket, scanner, scanner stand and AIO Computer imagePROGRAF TX-Series Printer Driver, Quick Utility Toolbox, Print Plug-in for Office, Extended Survey Program and Poster Artist Lite other software is available to download from Canon's

Printer, 1 x Print Head, 1 x Maintenance Cartridge, 3" Paper Core Attachment, EU & UK Power Cable, 1 Set of Starter Ink Tanks, Set Audenment, EO & ON Power Cable, Fee Of Starter Ink Tainks, Set Up Guide, Safety/Standard, Software CD-ROM (OSX/Windows), PosterArtist Lite CD-ROM, EU Biocide Sheet, Eurasian Economic Union Sheet, Important Information Sheet, Quick Guide and Print head Alignment Sheet

Roll Unit: RU-42 Stacker: SS-41 2/3" Roll Holder: RH2-45

web site.

Print Head: PF-06 Ink Tanks: PFI-110(160ml), PFI-310(330ml), PFI-710(700ml) Cutter Blade: CT-07 Maintenance Cartridge: MC-30

NOTES & RECOMMENDATIONS