

## THE NEXT STANDARD OF ENGINEERING



Shown with TX Stacker



Shown with MultiPositional  
Catch Basket



**imagePROGRAF  
TX-3000**

# imagePROGRAF TX-3000

## SPECIFICATIONS

### Print Head

PF-06

### Technology

FINE (Photolithography Inkjet Nozzle Engineering)

### Print Resolution (Max.)

2400 x 1200 dpi

### Line Accuracy\*

±0.1% or Less

### Minimum Line Weight\*\*

0.02 mm

### Number of Nozzles

Matte Black: 5,120 Nozzles

Other Colors: 2,560 Nozzles per Color

### Droplet Size

5 Picoliter

### Nozzle Pitch (Head Resolution)

1200 dpi x Two Rows

### Print Head Swath

1.07 inch

### Ink Type

Pigment: Matte Black (MBK), Cyan (C), Magenta (M), Yellow (Y), Black (BK)

### Ink Tank

Shipped with Printer: PFI-310 (330 ml) MBK; PFI-110 (160 ml) BK, C, M, Y

Replacement: PFI-110 (160 ml), PFI-310 (330 ml), or PFI-710 (700 ml)

### Ink Supply Method

Tubing System with Sub-tanks for Continuous Ink Supply

### Nozzle Recovery System

Non-firing Nozzle Detection and Compensation

### Printer Controller

L-COA PRO

### Printer RAM

128 GB (Virtual), 2 GB (Physical)

### Hard Drive

500 GB

### Mailboxes (User Job Storage)

One Common Inbox; 29 User Inboxes (Password-protected)

### Media Feed

Roll Feed: One Roll, Front-loading, Front Output

### Media Width

Roll Feed: 8"-36" (203.2mm -914.4mm)

Cut Sheet: 8"-36" (203.2 mm -914.4mm)

### Printable Margins

Roll Feed: All Sides: 0.12" (3 mm) or 0" for Borderless

### Maximum Print Length (Single Page)†

Roll Feed: 59' (18 m)

Cut Sheet: 63" (1.6 m)

### Borderless Printing Widths (Roll Media Only)

8", 10", 12", 14", 16", 17", 20", 24", 30", 36", B4 (10.12"/257 mm), A3 (11.69"/297 mm), A3+ (12.95"/329 mm), A2 (16.54"/420 mm), B2 (20.28"/515 mm), A1 (23.39"/594 mm), B1 (28.66"/728 mm), A0 (33.11"/841 mm)

### Media Cutter

Durable Dual-Blade Rotary Cutter

### Media Thickness

0.07 - 0.8 mm

### Media Core Sizes

2" and 3" Core Adapters Included

### Maximum Roll Outer Diameter

6.7" (170 mm)

### Media Output Options

TX Stacker

Multipositional Catch Basket

### Printing Software Utilities

Accounting Manager, Apple AirPrint,†† Canon Print Service, Device Management Console, Direct Print & Share, Free Layout Tool, imagePROGRAF Printer Driver for Windows®/Mac®, Media Configuration Tool, PosterArtist Lite for Windows, Printer Driver Extra Kit for Windows/Mac (Free Print Utility Layout, Advanced Preview), Optimized Driver for AutoCAD, Print Plug-in for Microsoft® Word/Excel/PowerPoint® for Windows, Quick Utility Toolbox

### Operating System

Windows 7 (32/64 bit), Windows 8.1 (32/64 bit), Windows 10 (32/64 bit), Windows Server 2008 R2, (32/64 bit), Windows Server 2012 (64 bit), Windows Server 2012 R2 (64 bit), Windows Server 2016 (64 bit), Macintosh OS X v10.10.5-v10.12.x

### Print Language

Printer: SGRaster, HP-GL/2, HP RTL, PDF, JPEG

### Interface

Standard (Built-in): USB 2.0 Hi-Speed, 10/100/1000Base-T/TX, Wireless LAN (IEEE 802.11 b/g/n)■

### Direct USB Thumb Drive Printing

### Acoustic Noise

Operation: 51 dB (A) or Less

Standby: 35 dB (A) or Less

Acoustic Power: 6.9Bels or Less

### Power Supply

AC 100-240V (50-60 Hz)

### Power Consumption

Maximum: 105 W or Less

Standby: 3.6 W or Less

Power Off: 0.3 W or Less (Executive Order Compliant)

### Certifications

#### Electrical Safety Regulations

C TÜVus (U.S.A.), C TÜVus (Canada)

#### Electromagnetic Interface Regulations

FCC Part 15B (U.S.A.), IC (Canada)

#### Radio Regulations

FCC Part 15C (U.S.A.), IC (Canada)

#### Environmental Certifications

ENERGY STAR® (Worldwide)

### Operational Environment

Temperature: 59° - 86° F (15° - 30° C)

Relative Humidity: 10 - 80% (No Condensation)

### Printer Dimensions (H x W x D) and Weight

(With Stacker Opened)

46.0" x 54.7" x 46.8" Approx. 257 lb.

### Printer Dimensions (H x W x D) and Weight

(With Basket Opened)

46.0" x 54.7" x 38.7" Approx. 231 lb.

### Package Dimensions (H x W x D) and Weight

(With Stand and Pallet)

41.8" x 63.2" x 35.6" Approx. 337 lb.

### Stacker

11.5" x 49.2" x 35.7" Approx. 53 lb.

### Roll Unit

18.1" x 60.0" x 22.1" Approx. 57 lb.

### Options

• Multifunction Roll System (RU-32)

• 2"/3" Roll Holder Set (RH2-34)

• PosterArtist

### User-Replaceable Items

• Ink Tank (PFI-110/PFI-310/PFI-710)

• Print Head (PF-06)

• Maintenance Cartridge (MC-30)

• Cutter Blade (CT-07)

### What's In The Box

Printer, TX Stacker or Catch Basket, Stand, 2"/3" Core Media Spool (Adapters Included), Power Cord, Tools and Screws, Print Head, Maintenance Cartridge (Installed), 5 Ink Tanks (330 ml: MBK, 160 ml: BK/C/M/Y), Sample Heavyweight Coated Paper (A2/5 Sheets), Ethernet Card (built-in), USB 2.0 High-speed Interface, USB Connection Sheet, iWR Service Terms Leaflet, User Manual, Quick Setup Guide, User Software CD for Windows (Printer Driver Utilities), PosterArtist Lite CD, User Registration Card

\* Line accuracy repeatability is guaranteed after a user performs necessary adjustment and under the same environmental conditions. Applies to media for line drawing (Plain Paper, Coated Paper, CAD Translucent Matte Film, and CAD Tracing Paper) only.

\*\* Theoretical value based on data resolution.

† The maximum printable length varies depending on the application, OS, and RIP used.

†† To be supported in 2018 by updating firmware.

■ Wireless printing requires a working network with wireless 802.11b/g or 802.11n capability. Wireless performance may vary based on terrain and distance between the printer and wireless network clients.

USA.CANON.COM/LARGEFORMAT



Note: TX-3000 on front page shown with optional Multifunction Roll System. Canon and imagePROGRAF are registered trademarks of Canon Inc. in the United States and may also be registered trademarks or trademarks in other countries. All other referenced product names and marks are trademarks of their respective owners. All printer output and screen images are simulated. Specifications and availability subject to change without notice. Not responsible for typographical errors.

©2020 Canon U.S.A., Inc. All rights reserved.

1020RI-TX3000SS-PDF-IH

