



# The Fastest imagePROGRAF. Ever.

Up to 4 D Prints/Minute\*  
Up to 244 D Prints/Hour\*\*

Integrated 100-Print  
Capacity Top Stacker

Dual-Roll Intelligent Media-Handling System  
that Detects Media Type, Width, and Length



imagePROGRAF  
TZ-30000

## PRINTER SPECIFICATIONS

### Print Head

PF-06

### Technology

FINE (Photolithography Inkjet Nozzle Engineering)

### Print Resolution (Max.)

2400 x 1200 dpi

### Line Accuracy

±0.1% or Less

### Minimum Line Weight<sup>■</sup>

0.02 mm

### Number of Nozzles

**Matte Black:** 5,120 Nozzles

**Other Colors:** 2,560 Nozzles per Color

### Droplet Size

5 Picoliter

### Nozzle Pitch (Head Resolution)

1200 dpi x Two Rows

### Print Head Swath

1.07 inch

### Ink Type

**Pigment:** Matte Black (MBK), Cyan (C), Magenta (M), Yellow (Y), Black (BK)

### Ink Tank

**Shipped with Printer:** 330ml MBK; 160ml BK,C,Y,M

**Replacement:** PFI-340 (330 ml), PFI-740 (700 ml)

### Ink Supply Method

Tubing System with Sub-tanks for Continuous Ink Supply

### Nozzle Recovery System

Non-firing Nozzle Detection and Compensation

### Printer Controller

L-COA PRO

### Printer RAM

128 GB (Virtual), 2 GB (Physical)

### Hard Drive

500 GB

### Media Feed

**Roll Feed:** Two Rolls, Front Loading

**Cut Sheet:** Front Loading

### Media Width

**Roll Feed:** 8" - 36" (203 mm - 914 mm)

**Cut Sheet:** 8" - 36" (203 mm - 914 mm)

### Printable Margins

**Roll Feed:** All Sides: 0.12" (3 mm) or 0" for Borderless

### Borderless Printing Widths (Roll Media Only)

Custom roll width 8" - 36" with micro margin technology

### Media Cutter

Durable Dual-Blade Rotary Cutter

### Media Thickness

0.07 mm - 0.8 mm

### Media Core Sizes

2" and 3" Core Adapters Included

### Maximum Roll Outer Diameter

6.9" or Less

### Media Output

**Front Output:** Basket

**Top Output:** Top Delivery Tray

### Printing Software Utilities

Accounting Manager, Canon Print Service, Device Management Console, Direct Print Plus, Printer Driver Extra Kit, Free Layout Plus, Media Configuration Tool, PosterArtist Lite for Windows, PosterArtist (optional purchase), CPP Publisher Select, Canon Printer Driver, CPP Driver Select, Optimized Driver for AutoCAD

### Operating System

Windows<sup>®</sup> 7 (32/64-bit), Windows 8.1 (32/64-bit), Windows 10 (32/64-bit), Windows Server 2008 R2, (32/64 bit), Windows Server 2012 (64-bit), Windows Server 2016 (64-bit), Macintosh<sup>®</sup> OS X v10.10.5 - v10.12x

### Print Language

**Printer:** SGRaster, HP-GL/2, HP RTL, PDF, JPEG

### Interface

#### USB B Port

**Type:** Built-in (Hi-speed USB)

**Mode:** Full Speed (12-Mbit/sec.), High Speed (480-Mbit/sec.), Bulk Transfer  
Connector Type: Series B (4 Pins)

**USB A Port:** USB Memory (Direct Print)

#### Gigabit Ethernet

**Type:** Built-in

**Standard:** IEEE 802.3u 100Base-TX/Auto-Negotiation  
IEEE 802.3ab 1000Base-T/Auto-Negotiation  
IEEE 802.3x Full Duplex

**Protocol:** SNMP, HTTP, TCP/IP (IPv4/IPv6), FTP

#### Wireless LAN<sup>■</sup>

**Standard:** IEEE802.11n/IEEE802.11g/IEEE802.11b

**Security:** WEP (64/128-bit)  
WPA-PSK (TKIP/AES)  
WPA2-PSK (TKIP/AES)

### Acoustic Noise

**Operation:** 52 dB (A) or Less

**Standby:** 35 dB (A) or Less

**Acoustic Power:** 7 Bels or Less

### Power Supply

AC 100 - 240 V (50 - 60 Hz)

## imagePROGRAF TZ-30000

### Power Consumption

**Maximum:** 68 W or Less

**Standby:** 3.6 W or Less

**Power Off:** 0.3 W or Less

### Certifications

International ENERGY STAR<sup>®</sup> Program (WW), TUV, CB, EPEAT

### Operational Environment

**Temperature:** 59° F - 86° F (15° C - 30° C)

**Relative Humidity:** 10 - 80% (No Condensation)

### Printer Dimensions (H x W x D) and Weight

47" x 61" x 38"; 456 lb. (Approx.)

### Package Dimensions (H x W x D) and Weight

54" x 67" x 37"; 604 lb. (Approx.)

### Options

- 2"/3" Roll Holder Set (RH2-34)
- PosterArtist

### User-Replaceable Items

- Ink Tank (PFI-340/PFI-740)
- Print Head (PF-06)
- Maintenance Cartridge (MC-30)

### What's In The Box

Printer, Top Output Stacker, Basket, 2"/3" Core Media Spool (Adapters Included), Power Cord, Tools and Screws, Print Head, Maintenance Cartridge (Installed), 5 Ink Tanks (330 ml MBK, 160 ml: BK/C/M/Y), Ethernet Card (built-in), USB 2.0 High-speed Interface, USB Connection Sheet, iWR Service Terms Leaflet, User Manual, Quick Setup Guide, User Software CD for Windows (Printer Drive Utilities), PosterArtist Lite CD, User Registration Card, Warranty Statement

- \* 14 seconds for an ANSI D print and 4 ANSI D prints/minute speed measured after first print in Fast Q5 mode, using plain paper.
- \*\* All speeds measured using plain paper, Fast Q5 mode. The 244 ANSI D prints/hour is measured from when the first print begins printing.
- Theoretical value based on data resolution.
- Wireless printing requires a working network with wireless 802.11b/g or 802.11n capability. Wireless performance may vary based on terrain and distance between the printer and wireless network clients.

For more information, reach us at  
315.437.5111 • [www.planandprint.com](http://www.planandprint.com) • [sales@planandprint.com](mailto:sales@planandprint.com)



Canon and imagePROGRAF are registered trademarks of Canon Inc. in the United States and may also be registered trademarks or trademarks in other countries. All other referenced product names and marks are trademarks of their respective owners. Specifications and availability subject to change without notice. Not responsible for typographical errors.  
©2021 Canon U.S.A., Inc. All rights reserved.  
0321-TZ-30000SS-PDF-IH

