

REDEFINING THE  
LARGE-FORMAT  
PRINTER



**imagePROGRAF  
TM-300**



## Print Head

PF-06

## Technology

FINE (Photolithography Inkjet Nozzle Engineering)

## Print Resolution (Max.)

2400 x 1200 dpi

## Line Accuracy\*

±0.1% or Less

## Minimum Line Weight\*\*

0.02 mm

## Number of Nozzles

Matte Black: 5,120 Nozzles

Other Colors: 2,560 Nozzles per Color

## Droplet Size

5 Picoliter

## Nozzle Pitch (Head Resolution)

1200 dpi x Two Rows

## Print Head Swath

1.07 inch

## Ink Type

Pigment: Matte Black (MBK), Cyan (C), Magenta (M), Yellow (Y), Black (BK)

## Ink Tank

Shipped with Printer: MBK (130 ml), BK, C, M, Y (90 ml)

Replacement: PFI-120 (130 ml) or PFI-320 (300 ml)

## Ink Supply Method

Tubing System with Sub-tanks for Continuous Ink Supply

## Nozzle Recovery System

Non-firing Nozzle Detection and Compensation

## Printer Controller

L-COA PRO

## Printer RAM

2 GB

## Media Feed

Roll Feed: One Roll, Top-loading, Front Output

## Media Width

Roll Feed: 8"-36" (203 mm - 914 mm)

Cut Sheet: 8"-36" (203 mm - 914 mm)

## Printable Margins

Roll Feed: All Sides: 0.12" (3 mm) or 0" for Borderless

## Maximum Print Length (Single Page)†

Roll Feed: 59' (18 m)

Cut Sheet: 63" (1.6 m)

## Borderless Printing Widths (Roll Media Only)

8", 10", 12", 14", 16", 17", 20", 24", 30", 36",  
B4 (10.12"/257 mm), A3 (11.69"/297 mm),  
A3+ (12.95"/329 mm), A2 (16.54"/420 mm),  
B2 (20.28"/515 mm), A1 (23.39"/594 mm),  
B1 (28.66"/728 mm), A0 (33.11"/841 mm)

## Media Cutter

Durable Dual-Blade Rotary Cutter

## Media Thickness

0.07 - 0.8 mm

## Media Core Sizes

2" and 3" Core Adapters Included

## Maximum Roll Outer Diameter

5.9" (150 mm)

## Media Output

Basket (Standard)

## Printing Software Utilities

Accounting Manager, Apple AirPrint, Canon Print Service, Device Management Console, Direct Print & Share, Free Layout Plus, imagePROGRAF Printer Driver for Windows®/Mac®, Media Configuration Tool, PosterArtist Lite for Windows, Canon PRINT Inkjet Selphy, Easy-Photo PrintEditor,† Optimized Driver for AutoCAD, Free Layout

## Operating System

Windows 7 (32/64 bit), Windows 8.1 (32/64 bit), Windows 10 (32/64 bit), Windows Server 2008 R2, (32/64 bit), Windows Server 2012 (64 bit), Windows Server 2012 R2 (64 bit), Windows Server 2016 (64 bit), Macintosh OS X v10.10.5-v10.12x

## Print Language

Printer: SGRaster, HP-GL/2, HP RTL, JPEG

## Interface

Standard (Built-in): USB 2.0 Hi-Speed, 10/100/1000Base-T/TX, Wireless LAN (IEEE 802.11 b/g/n)■

## Acoustic Noise

Operation: 44 dB (A)

Standby: 35 dB (A) or Less

Acoustic Power: 6.0Bels

## Power Supply

AC 100-240V (50-60 Hz)

## Power Consumption

Maximum: 69 W or Less

Standby: 3.6 W or Less

Power Off: 0.3 W or Less (Executive Order Compliant)

## Certifications

### Electrical Safety Regulations

C TUVus (U.S.A.), C TUVus (Canada)

### Electromagnetic Interface Regulations

FCC Part 15B (U.S.A.), IC (Canada)

### Radio Regulations

FCC Part 15C (U.S.A.), IC (Canada)

### Environmental Certifications

ENERGY STAR® (Worldwide)

## Operational Environment

Temperature: 59° - 86° F (15° - 30° C)

Relative Humidity: 10 - 80% (No Condensation)

## Printer Dimensions (H x W x D) and Weight

(With Basket Opened)

42" x 51" x 34" Approx. 130 lb.

## Package Dimensions (H x W x D) and Weight

With Stand, Basket, and Pallet

38" x 58" x 36" Approx. 229 lb.

## Options

- 2"/3" Roll Holder Set (RH2-35)

- PosterArtist

## User-Replaceable Items

- Ink Tank (PFI-120/PFI-320)
- Print Head (PF-06)
- Maintenance Cartridge (MC-31)
- Cutter Blade (CT-08)

## What's In The Box

Printer, Basket, Stand, 2"/3" Core Media Spool (Adapters Included), Power Cord, Tools and Screws, Print Head, Maintenance Cartridge (Installed), 5 Ink Tanks (130 ml: MBK, 90 ml: BK/C/M/Y), Sample Heavyweight Coated Paper (A2/2 Sheets), Ethernet Card (built-in), USB 2.0 High-speed Interface, USB Connection Sheet, iWR Service Terms Leaflet, User Manual, Quick Setup Guide, User Software CD for Windows (Printer Driver Utilities), PosterArtist Lite CD, User Registration Card

\* Line accuracy repeatability is guaranteed after a user performs necessary adjustment and under the same environmental conditions. Applies to media for line drawing (Plain Paper, Coated Paper, CAD Translucent Matte Film, and CAD Tracing Paper) only.

\*\* Theoretical value based on data resolution.

† The maximum printable length varies depending on the application, OS, and RIP used.

†† To be supported in December 2018.

■ Wireless printing requires a working network with wireless 802.11b/g or 802.11n capability. Wireless performance may vary based on terrain and distance between the printer and wireless network clients.

For more information, reach us at  
315.437.5111

www.planandprint.com  
sales@planandprint.com

imagePROGRAFplotter.com



As an ENERGY STAR® Partner, Canon U.S.A., Inc. has qualified this model as meeting the ENERGY STAR energy efficiency criteria through an EPA recognized certification body. ENERGY STAR and the ENERGY STAR mark are registered trademarks owned by the U.S. Environmental Protection Agency. Canon and imagePROGRAF are registered trademarks of Canon Inc. in the United States and may also be registered trademarks or trademarks in other countries. All other referenced product names and marks are trademarks of their respective owners. All printer output and screen images are simulated. Specifications and availability subject to change without notice. Not responsible for typographical errors.

©2018 Canon U.S.A., Inc. All rights reserved.

1218R1-TM300SS-PDF-IH

